

VME type preamplifier power supply with 4 plugs
Standard 9-pin D connectors

Overview

Supply voltage for preamplifier
± 12 V (50 mA or more) and
± 24 V (50 mA or more) to each plugs.

The output connectors are all 4 plugs and 9-pin D,
and the pin arrangement is NIM standard compliant.

This module derives its power from VME powered crates
such as APV9007

Specification

Number of Plugs	4 (Four)
Connector	Female, 9-pin D on the front panel With anti-removal fittings
Current	±12V: 50 mA or more ±24V: 50 mA or more
Pin Assignment	1: Ground 2: Ground 3: No Connection (Disconnected) 4: +12 V 5: No Connection (Disconnected) 6: -24 V 7: +24 V 8: No Connection (Disconnected) 9: -12 V
LED	POWER
Dimensions	VME-standard 6U, Single-width 20 (W) x 26(H) x 187(D) unit: mm
Weight	About 0.5 kg
Operating Condition	Operating temperature 0 to 40 degrees Non condensing



*Images is for illustration purpose.
*Please note that contents may change without prior notice.

Website



Manufacture of Radiation and Radioactivity measurement devices

TechnoAP Co., Ltd.

2976-15 Mawatari, Hitachinaka-shi, Ibaraki, 312-0012, Japan

☎ +81-29-350-8011

📠 +81-29-352-9013

✉ order@techno-ap.com